

MOD. 050F-ek				050F-ek	
I	F	GB	D		
DATI TECNICI	DONNEES TECHNIQUES	SPECIFICATIONS	TECHNISCHE DATEN		
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN LxTxH	600x650x820	mm
CAPACITA' ORARIA piatti/ora	DEBIT/H assiettes/H	WASHING CAPACITY dishes/H	STUNDENLEISTUNG Teller/Stunde	540/360/270 1080/540/360	Nr.
CAPACITA' ORARIA cestelli/ora	DEBIT/H casiers/H	WASHING CAPACITY baskets/H	STUNDENLEISTUNG Körbe/Stunde	30/20/15 60/30/20	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	2÷3÷4 1÷2÷3	MIN.
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORBAMAßE	50 x 50	cm
NUM.PIATTI /CESTELLO	NUM.ASSIETTES POUR CASIER	PLATES PER BASKETS	N°.TELLER PRO KORB	12÷18	Nr.
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFLÄCHENHÖHE	370	mm
LUCE DI CARICO	OUVERTURE DE CHARGEMENT	CLEARANCE	DURCHGANGSHÖHE	330	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	VERSORGUNGSPANNUNG	230 V1N~50Hz	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	650	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	2000	W
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	3000	W
POTENZA NOMINALE	PUISSANCE NOMINALE	TOTAL RATING	GESAMTVERBRAUCH	3650	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMAUFNAHME	20	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKFÜLLUNG	18	Lt
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERINHALT	5	Lt
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RINÇAGE	RINSE AID DISPENSER	NACHSPÜLMITTELDOSIERANLAGE	si-oui-yes-ja	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLUß	45 ÷ 55	°C
PORTATA ACQUA POMPA	DEBIT EAU MOTEUR	PUMP DELIVERY	UMWALZUNG WASCHPUMPE	300	l./min
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	CYCLE WATER CONSUMPTION	WASSERVERBRAUCH - ZYKLUS	2.60	l
CONSUMO ACQUA PER ORA	CONSOMMATION EAU ORAIRE	HOOR WATER CONSUMPTION	WASSERVERBRAUCH - STUNDE	52	l
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	2 ÷ 4	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOLHENE WASSERHÄRTE	5 ÷ 10	°F
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RINÇAGE	RINSING WATER TEMPERATURE	SPÜLWASSERTEMPERATUR	80 ÷ 90	°C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFROHRWEITE	3/4"	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFROHRWEITE	32 mm - 1"1/4	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	68	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	78	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	VERPACKUNGABMESSUNGEN	640x740x1000	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GERÄUSCH	<56	dB(A)
DOTAZIONI OPTIONAL	ACCESSOIRES	OPTIONAL	OPTIONAL		
ADDOLCITORE	ADOUCCISSEUR	WATER SOFTENER	ENTHÄRTER	OPTION	
POMPA DI SCARICO	POMPE DE VIDANGE	DRAIN PUMP	ABLAUFPUMPE	30	W
DOSATORE DI LAVAGGIO	DOSEUR DE PRODUIT DE LAVAGE	WASH AID DISPENSER	WASCHMITTELDOSIERANLAGE	OPTION	